



GU10



GU5.3

You have great products, and they deserve to be showcased. Let your customers see them. A small lamp that packs a large punch: QLS MR16 and GU10 lamps are perfect for retail, hospitality, and track light applications. Providing exceptional CRI and compatible with most MR16 sockets, QLS LED MR16 lamps are the right choice for your business.

FEATURES

- Sturdy, plastic and aluminum design
- Smooth, even light distribution
- Dimmable to 0%
- GU10 and MR16 form factors available
- Damp and enclosed location rated
- High CRI and COB versions available upon request
- Reduced heat output
- Life: L70 25,000 Hours

APPLICATIONS

This product family can be effectively used in 120 Volt GU10 and 12V MR16 applications. Commercial, industrial, retail, residential and healthcare applications.

ITEM NUMBER GUIDE ex. LGU10D5030EF

| Family | Dimmable | Watt | CCT | Energy Star | Beam Spread |
|--------|----------|------|-----|-------------|-------------|
| LGU10 | D | 50 | 27 | E | F |
| LMR16 | | | 30 | E | N |
| | | | 40 | | |
| | | | 50 | | |

↓ ↓ ↓ ↓ ↓ ↓
 LGU10 D 50 30 E F

MR16 GU10 - 120V



| QLS | Watt. | Lumens | Eff L/W | Beam Angle | CBCP | Dim. | CCT | CRI | Case QTY | Watt. Equiv. | Life | H (In) | W (In) | Energy Star |
|--------------|-------|--------|---------|------------|------|------|------|-----|----------|--------------|-------|--------|--------|-------------|
| LGU10D5027EF | 6.0 | 500 | 83 | 40 | 1160 | Yes | 2700 | >80 | 48 | 50 | 25000 | 2.2 | 2.0 | Yes |
| LGU10D5030EF | 6.0 | 500 | 83 | 40 | 1069 | Yes | 3000 | >80 | 48 | 50 | 25000 | 2.2 | 2.0 | Yes |
| LGU10D5040EF | 6.0 | 500 | 83 | 40 | 1126 | Yes | 4000 | >80 | 48 | 50 | 25000 | 2.2 | 2.0 | Yes |
| LGU10D5050EF | 6.0 | 500 | 83 | 40 | 1110 | Yes | 5000 | >80 | 48 | 50 | 25000 | 2.2 | 2.0 | Yes |
| LGU10D5027EN | 6.0 | 500 | 83 | 20 | 3296 | Yes | 2700 | >80 | 48 | 50 | 25000 | 2.2 | 2.0 | |
| LGU10D5030EN | 6.0 | 500 | 83 | 20 | 3296 | Yes | 3000 | >80 | 48 | 50 | 25000 | 2.2 | 2.0 | |
| LGU10D5040EN | 6.0 | 500 | 83 | 20 | 3296 | Yes | 4000 | >80 | 48 | 50 | 25000 | 2.2 | 2.0 | |
| LGU10D5050EN | 6.0 | 500 | 83 | 20 | 3296 | Yes | 5000 | >80 | 48 | 50 | 25000 | 2.2 | 2.0 | |

MR16 GU5.3 - 12V



| QLS | Watt. | Lumens | Eff L/W | Beam Angle | CBCP | Dim. | CCT | CRI | Case QTY | Watt. Equiv. | Life | H (In) | W (In) | Energy Star |
|--------------|-------|--------|---------|------------|------|------|------|-----|----------|--------------|-------|--------|--------|-------------|
| LMR16D5027EF | 7.1 | 500 | 70 | 40 | 1160 | Yes | 2700 | >80 | 48 | 50 | 25000 | 1.8 | 2.0 | Yes |
| LMR16D5030EF | 7.1 | 525 | 74 | 40 | 1069 | Yes | 3000 | >80 | 48 | 50 | 25000 | 1.8 | 2.0 | Yes |
| LMR16D5040EF | 7.1 | 525 | 74 | 40 | 1126 | Yes | 4000 | >80 | 48 | 50 | 25000 | 1.8 | 2.0 | Yes |
| LMR16D5050EF | 7.1 | 550 | 77 | 40 | 1110 | Yes | 5000 | >80 | 48 | 50 | 25000 | 1.8 | 2.0 | Yes |
| LMR16D5027EN | 7.1 | 500 | 70 | 20 | 3296 | Yes | 2700 | >80 | 48 | 50 | 25000 | 1.8 | 2.0 | |
| LMR16D5030EN | 7.1 | 525 | 74 | 20 | 3296 | Yes | 3000 | >80 | 48 | 50 | 25000 | 1.8 | 2.0 | |
| LMR16D5040EN | 7.1 | 525 | 74 | 20 | 3296 | Yes | 4000 | >80 | 48 | 50 | 25000 | 1.8 | 2.0 | |
| LMR16D5050EN | 7.1 | 550 | 77 | 20 | 3296 | Yes | 5000 | >80 | 48 | 50 | 25000 | 1.8 | 2.0 | |